



Material Safety Data Sheet

Product Name: Azuza Soft Rock

HMIS CODES: H F R P
0 0 0 B

Manufacturer's Name: Acrylatex Coatings & Recycling, Inc.
1000 W. Kirkwall Rd.
Azusa, CA 91702
Phone 626.812.0191
Fax 626.812.0415
Emergency Phone 714.308.1821
Web: www.Acrylatex.com
Email: sales@acrylatex.com

Section I: Product Identification

Product Name: Azuza Soft Rock. Recycle Content Decorative Landscaping Ground Cover.
Product Class: Pigmented Latex Solid for Exterior use. Contains at least 98% post consumer latex paint.

Section II: Hazardous Ingredients

INGREDIENT CAS #	%BY WEIGHT	EXPOSURE LIMITS AND SOURCE	VAPOR PRESSURE mm of Hg
QUARTZ (as Quartz) CAS#: 14808-60-7		0.1 mg/m ³ 0.1 mg/m ³ ACGIH	OSHA PEL
Zinc Oxide (1) CAS#: 1314-13-2	1-5%	Total Dust: 10mg/m ³ OSHA PEL 10 mg/m ³ ACGIH TLV Respiration Fraction: 5 mg/m ³ OSHA PEL	nil
Calcium Carbonate CAS#: 1317-65-3	1-10%	Total Dust: 15 mg/m ³ OSHA PEL 10 mg/m ³ ACHIH TLV Respiration Fraction: 5 mg/m ³ OSHA PEL	nil

Kaolin CAS#: 66402-68-4	1-10%	Total Dust: 10 mg/m ³ OSHA PEL 10 mg/m ³ OCGIH TLV Respiration Fraction: 5mg/m ³ OSHA PEL	nil
Titanium Dioxide CAS#: 13463-67-7	5-25%	Total Dust: 10 mg/m ³ OSHA PEL 10 mg/m ³ ACGIH TLV Respiration Fraction: 5 mg/m ³ OSHA PEL	nil

- (1) This ingredient(s) is a toxic chemical subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and of 40 CFR 372.
- (2) Carcinogenic: NTP_ IARC X OSHA_ WISHA_

Section III: Physical Data

BOILING RANGE: N/A WEIGHT PER Cubic Foot: 8.5-11.0 lbs
VAPOR DENSITY: Heavier than Air EVAPORATION RATE: Slower than ether
Coating V.O.C. < 25 g/L Solubility in Water: Non
Specific Gravity: 1.4 approx. LC/50 > 750mg/l
Appearance and Odor: Colored Solid Rock like pebbles, mild odor.

Section IV: Fire and Explosion Hazard Data

FLAMMABILITY CLASSIFICATION: OSHA: None FLASH POINT: >200
DOT: None LEL: None

EXTINGUISHING MEDIA:
Foam, CO₂, Dry Chemical and or Water Fog

UNUSUAL FIRE AND EXPLOSION DATA: None.

SPECIAL FIREFIGHTING AND EXPLOSION DATA: The use of self-contained breathing apparatus is recommended for fire fighters.

Section V: Health Hazard Data

ACUTE HEALTH HAZARDS: None

CHRONIC HEALTH HAZARDS: None

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: Crystalline silica has been classified as a probable carcinogenic for humans (2a) by IARC.

PRIMARY ROUTE(S) OF ENTRY: Dermal (skin), Inhalation (airway)

EMERGENCY AND FIRST AID PROCEDURES: If splashed into eyes, flush eyes with clear water for 15 minutes or until irritation subsides, consult a physician as may be required. In case of skin contact, remove any contaminated clothing, and wash skin with soap and warm water. If inhaled, move to fresh air. If ingested, do not induce vomiting, call a physician.

Section VI: Reactivity Data

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur

HAZARDOUS DECOMPOSITION PRODUCTS: Vinyl acetate monomer, CO₂, and possibly CO.

CONDITIONS TO AVOID: Submersion under water for periods over 1 week. Temperatures above 130° F.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents, sulfuric acid and other dehydrating agents.

Section VII: Spill or Leak Procedures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Sweep up area affected and place back into shipping container or place back into planter area.

WASTE DISPOSAL METHOD: This is a Non Hazardous Material per State and Federal regulations. If disposal is needed, you may place in regular trash. Recycle where available.

Section VIII: Safe Handling and Use Information

RESPIRATORY PROTECTION: None required. But if dust is being generated during application, use appropriate dust mask.

VENTILATION: Use as supplied in ambient outdoor areas. No special ventilation is required.

PROTECTIVE GLOVES: Cotton or leather gloves are adequate.

EYE PROTECTION: Safety glasses if necessary.

OTHER PROTECTIVE EQUIPMENT: As needed to avoid repeated or prolonged exposure.

HYGIENIC PRACTICES: After contact wash with soap and water prior to eating, drinking, smoking, or using toilet facilities.

Section IX: Special Precautions

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep container closed when not in use. Do not handle or store near heat, or strong oxidizing agents. Avoid contact with skin and eyes. Remove contaminated clothing and laundry before reuse. Wash skin thoroughly with soap and water after contact.

Section X: Disclaimer

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind expressed or implied is made with respect to the information contained herein. Acrylatex Coatings & Recycling, Inc., does not assume any legal responsibility for use or reliance on the information supplied on this document.

Revised 10/20/10